



GREASE PUMPS

Alemite Grease pumps are designed to handle a wide range of applications, fluid viscosities and system pressures. Combined with Alemite Hose Reels, Dispensing Valves and Meters, Alemite Grease Pumps deliver lubricant from tanks, drums, totes and pails.

Pneumatic RAM - Stationary

Alemite Stationary RAM Pumps deliver fast, quiet and efficient operation. Capable of delivery up to 4.5 pounds per minute, RAM double acting grease pumps reduce line pulsation and allow lower operating pressure. They are designed for piped installations of moderate length.

FEATURES:



9950-A1

- 3” diameter air motor
- Recommended for piped installations up to 150 feet
- Meets OSHA noise requirements (85dB)
- Easy 360° adjustment of material outlet and air inlet
- May be used with or without lubricator
- Easy access air motor and spool – without removing downtube
- Flexible follower for straight or tapered containers
- Metric RAM pumps meet European CE standards
- Easy serviceability
- Air Inlet: 1/4” NPTF(f)

Product #	Drum Size	Material Outlet	Pump Ratio	Delivery	Follower	Cover	Weight
9940	120 Lb.	3/8” NPTF(f)	70:1	3.25 Lb./minute	338802	338371	28 Lb.
9949	400 Lb.	3/8” NPTF(f)	70:1	3.25 Lb./minute	338911	338163	32 Lb.
9950-I	120 Lb.	3/8” NPTF(f)	50:1	4.5 Lb./minute	338802	338371	19 Lb.
9950-A1	120 Lb.	3/8” NPTF(f)	50:1	4.5 Lb./minute	338802 (included)	338371 (included)	32 Lb.
9979	400 Lb.	3/8” NPTF(f)	50:1	4.5 Lb./minute	338911	338163	25 Lb.
9979-A	400 Lb.	3/8” NPTF(f)	50:1	4.5 Lb./minute	338911 (included)	338163 (included)	49 Lb.
9950-C1	20 Kg.	3/8” NPTF(f)	50:1	2.04 Kg./minute	338992	338982	18 Lb.
9950-I	50 Kg.	3/8” NPTF(f)	50:1	2.04 Kg./minute	338802	338371	19 Lb.
9950-D1	180 Kg.	3/8” NPTF(f)	50:1	2.04 Kg./minute	338911	338984	23 Lb.
9930	Bulk	3/8” NPTF(f)	50:1	4.5 Lb./minute	Not required	Not required	16 Lb.