

FL SWITCH SFN 6GT/2SX


Order No.: 2891398



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2891398>

Ethernet switch, 6 RJ45 ports, 10/100/1000 Mbps on all RJ45 ports, 2 multi-mode SC-D ports, 1 Gbps full duplex, autonegotiation (RJ45), autocrossing function, with signal contact and QoS, extended temperature range

Ethernet

Commercial data	
GTIN (EAN)	
sales group	K000
Pack	1 pcs.
Customs tariff	85176200
Catalog page information	Page 91 (AX-2011)

Product notes

WEEE/RoHS-compliant since: 01/02/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Interfaces	
Interface 1	Ethernet (RJ45)
No. of ports	6 (RJ45 ports)
Connection method	RJ45 female connector, auto negotiation and autocrossing

Transmission physics	Ethernet in RJ45 twisted pair
Transmission speed	10/100/1000 MBit/s (RJ45)
Interface 2	Fiber optic interface
No. of ports	2 (FO ports)
Connection method	SC duplex
Transmission physics	Multimode glass fiber
Transmission speed	1000 MBit/s (SC-D, full duplex)
Transmission length	220 m (Glass fiber 62.5/125)
	550 m (Glass fiber 50/125)
Wavelength	850 nm
Interface 3	Potential-free signaling contact
Connection method	Plug-in/screw connection via COMBICON
Function	
Basic functions	Unmanaged switch / autonegotiation, complies with IEEE 802.3, store and forward switching mode
Status and diagnostic indicators	LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port
Network expansion parameters	
Cascading depth	Network, linear, and star structure: any
Maximum conductor length ((twisted pair)	100 m
Supply voltage	
Supply voltage	24 V DC (redundant)
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Supply voltage range	9 V DC ... 30.2 V DC
Typical current consumption	Typ. 350 mA
General data	
Width	50 mm
Height	120 mm
Depth	70 mm
Mounting type	DIN rail
Type AX	Block-oriented
Weight	425 g
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C (75 °C in preparation)

Ambient temperature (storage/transport)	-35 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (no condensation)
Permissible humidity (storage/transport)	5 % ... 95 % (no condensation)
Air pressure (operation)	86 kPa ... 108 kPa (up to 1500 m above mean sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above mean sea level)
Housing material	Aluminum
Noise emission	EN 61000-6-4
Noise immunity	EN 61000-6-2:2005

Certificates / Approvals



Certification	CUL, UL
Certification Ex:	CUL-EX LIS, UL-EX LIS

Accessories

Item	Designation	Description
Cable/conductor		
2832250	FL CAT5 PATCH 0,3	Patch cable, CAT5, assembled, 0.3 m
2832263	FL CAT5 PATCH 0,5	Patch cable, CAT5, assembled, 0.5 m
2832276	FL CAT5 PATCH 1,0	Patch cable, CAT5, assembled, 1.0 m
2832221	FL CAT5 PATCH 1,5	Patch cable, CAT5, assembled, 1.5 m
2832629	FL CAT5 PATCH 10,0	Patch cable, CAT5, assembled, 10.0 m
2832289	FL CAT5 PATCH 2,0	Patch cable, CAT5, assembled, 2.0 m
2832292	FL CAT5 PATCH 3,0	Patch cable, CAT5, assembled, 3.0 m
2832580	FL CAT5 PATCH 5,0	Patch cable, CAT5, assembled, 5.0 m
2832616	FL CAT5 PATCH 7,5	Patch cable, CAT5, assembled, 7.5 m
General		
0800886	E/NS 35 N	End clamp, width: 9.5 mm, color: gray
2832991	FL RJ45 PROTECT CAP	Dust protection caps for RJ45 female connector
2832865	FL SEC PAC 4TX	Layer1 security elements for four RJ45 network connections for use with patch boxes and panels

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;